

2x2plus specs



Power for everyone

The 2x2plus is a versatile 2U server that brings the flexibility of the disguise platform to smaller shows and fixed installations.

Warranties & Support

- Free software upgrades for the life of the machine
- 2 year return to base hardware warranty


Bundled accessories

Power Cable (IEC UK/EU/US), 2x Single Link DP to DVI adapters, Getting Started Guide.

Physical specifications

Packed Dimensions:	W 575mm 22.64"	H 210mm 8.27"	D 640mm 25.2"
Unit Dimensions:	W 430mm 16.93"	H 88mm 3.5"	D 495mm 19.48"
Unit + Rack Handles			D 520mm 20.5"
Rack Depth:			D 485mm 19.09"
Unit Weight:		11.9kg	26.3lbs
Packed Unit Weight:		17kg	37.5lbs

2x2plus specs



Hardware specifications

Voltage: 100-240V, 50-60Hz

Power Consumption:

350W @ 230V (max)

Operating System: Windows 8.1

Embedded Pro

CPU: Xeon Quad-Core 3.7Ghz

Memory: 8GB DDR3 RAM

Environmental Tolerances:

Temperature: 5-35°C (40°-95°F)

Humidity: 5%-95% (non-condensing)

Altitude: 0-8850 ft (0-2700m)

Mounting System:

2U 19" rack mount

Audio: On-board Audio or Pro Audio

Storage: 1× 80GB SSD

(Internal System Drive, Restore Drive)

1× 512GB SSD

System connectivity I/O

Video Output:

1× DVI DualLink (GUI)

2× DisplayPort 1.2 (2560 × 1600 max)

Video Input:

Choice of:

No capture card fitted (default)

or

3× HD-SDI or 2× 3G-SDI

or

1× DVI

Audio In/Out:

Choice of:

On-board audio (default)

or

Pro-Audio

2× Balanced XLR In/Out

1× 1/4" Headphones Jack

ADAT/SPDIF I/O

MIDI: 1× In, 1× Out

Ethernet: 2 × 1 Gigabit LAN

Data/Peripherals:

6× USB 2.0

2× USB 3.0